## **NOMAPACK® PAD**

NOMAPACK® PAD is a spacer available in various dimensions with removable or permanent glue. It is a spacer pad for separating sensitive goods or fixing them in place. The pads are pre-punched so that the desired length can be cut off simply and cleanly.

» Available with or without adhesive in various lengths and thicknesses

## PRODUCT FEATURES:

- » PE-LD foam
- » Supplied as lengths
- Water absorption1 vol.% after 40 days
- » Recyclable

## APPLICATIONS:

- » Cushioning
- » Spacing
- » Fixation







|          | Туре             | A<br>mm | B<br>mm   | C<br>mm     | Packaging unit pcs | Packaging unit*<br>m | Item code |
|----------|------------------|---------|-----------|-------------|--------------------|----------------------|-----------|
|          |                  |         | Remova    | ble adhes   | sive (white Rele   | ease)                |           |
| <b>%</b> | 50 × 10 HMR      | 50 ±3   | 10 ±2     | 50 ±8**     | 16.100             | 805                  | 3002213   |
| 00       | 50 × 20 HMR      | 50 ±3   | 20 ±2     | 50 ±8**     | 10.350             | 518                  | 3002215   |
| 00       | 50 x 50 HMR      | 50 ±3   | 50 ±3     | 50 ±8       | 4.025              | 201                  | 3002232   |
| 00       | 65 x 25 HMR      | 65 ±3   | 25 ±2     | 64 ±8       | 4.950              | 31 <i>7</i>          | 3002219   |
| 00       | 100 x 25 HMR     | 100 ±3  | 25 ±2     | 96 ±8       | 2.160              | 207                  | 3002220   |
| $\infty$ | 100 x 50 HMR     | 100 ±3  | 50 ±3     | 96 ±8       | 1.176              | 113                  | 3011417   |
|          |                  | Pe      | rmanent   | adhesive    | transparent R      | Release)             |           |
| 00       | 50 x 10 HMP      | 50 ±3   | 10 ±2     | 50 ±8**     | 16.100             | 805                  | 3002214   |
| <b>∞</b> | 50 × 20 HMP      | 50 ±3   | 20 ±2     | 50 ±8**     | 10.350             | 518                  | 3002216   |
| <b>%</b> | 50 x 50 HMP      | 50 ±3   | 50 ±3     | 50 ±8       | 4.025              | 201                  | 3002235   |
| <b>%</b> | 65 x 25 HMP      | 65 ±3   | 25 ±2     | 64 ±8       | 4.950              | 31 <i>7</i>          | 3002223   |
| <b>%</b> | 100 x 25 HMP     | 100 ±3  | 25 ±2     | 96 ±8       | 2.160              | 207                  | 3002224   |
| <b>%</b> | 100 x 50 HMP     | 100 ±3  | 50 ±3     | 96 ±8       | 1.176              | 113                  | 3011418   |
|          | $m^3/\Re = 0.68$ |         | <b>\$</b> | 190 * 790 ; | * 700 mm           | 3 <b>ജ</b> on        | pallet    |



Glue storage conditions: away from UV • Storage T°: 10-40 °C • Dry and dust free • 1 year from production date

We recommend the adequate tests be made in your laboratory, plant or otherwise to determine if this product meets all your specific requirements. The utilization of the goods shall thus be at the purchaser's own risk. The seller should refuse any responsibility regarding his intervention for direct and/or indirect damage potentially arising from this particular use. Only in case of product default, the seller shall not be liable for damages in excess of the purchase price of the product.



## NOMAPACK® PAD HALFMOON

The spacer profile with removable (D) or permanent (P) adhesive.



COLOUR Standard blue **LENGTH**1.000 ±20 mm



PACKAGING
Pieces in boxes



|    | Туре             | A<br>mm | B<br>mm       | Packaging unit pcs | Packaging unit<br>m | Item code |  |
|----|------------------|---------|---------------|--------------------|---------------------|-----------|--|
|    |                  | Re      | emovable d    | adhesive tape (w   | hite Release)       |           |  |
| 00 | 40 D             | 42 ±1   | 50            | 2.000              | 100                 | 3002225   |  |
| co | 50 D             | 51 ±2   | 50            | 1.200              | 60                  | 3002229   |  |
| 00 | 60 D             | 58 ±2   | 50            | 1.000              | 50                  | 3002236   |  |
|    |                  | Pe      | ermanent a    | dhesive tape (ye   | llow Release)       |           |  |
| 00 | 40 P             | 42 ±1   | 50            | 2.000              | 100                 | 3002228   |  |
| 00 | 50 P             | 51 ±2   | 50            | 1.200              | 60                  | 3002233   |  |
| 00 | 60 P             | 58 ±2   | 50            | 1.000              | 50                  | 3002237   |  |
|    | $m^3/\Re = 0.25$ |         | <b>1020</b> * | 600 * 400 mm       | 8 🥞                 | on pallet |  |



Glue stprage conditions: away from UV • Storage T°: 10-40 °C • Dry and dust free • 1 year from production date

warms mend the adequate tests be made in your laboratory, plant or otherwise to determine if this product meets all your specific requirements. The utilization of the goods shall the product meets all your specific requirements. The utilization of the goods shall the purchaser's own risk. The seller should refuse any responsibility regarding his intervention for direct and/or indirect damage potentially arising from this particular use. Only in case of product default, the seller shall not be liable for damages in excess of the purchase price of the product.