nmc

Last Update: 23.01.2025

# Cross-linked Thermoplastic foams produced by NMC

## 1. MATERIAL AND COMPANY IDENTIFICATION

Product name\*: Nomatec<sup>®</sup>.

Contact: Please contact your seller

or find your nearest dealer at www.nmc.eu/en/contact

**Utilization:** Sealing profiles, Industrial Components.

Note: The products are finished articles, they are therefore not subject to the directive 1907/2006 on

chemical substances and preparations

\* Not exhaustive list of concerned trade names, products inclusive

#### 2. HAZARD IDENTIFICATION

The thermoplastic foams produced by NMC do not constitute any risk to public health and environment if they are used as intended. Dust is produced while sawing, milling, grinding and sanding.

Molten product adheres to the skin and causes burns.

May contain residuals from physical inflammable blowing agent (hydrocarbons).

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Specification: Foams made of cross-linked polyethylene, which can contain additives like flame-

retardants and eventually provided with adhesive.

# 4. FIRST AID

Inhalation: Dust may be irritating to the upper part of the respiratory system. Move victim to fresh air and

obtain medical attention.

Skin contact: Molten product on the skin should be cooled rapidly with cold water, but not be pulled off.

Consult a doctor.

Eye contact: Dust can cause irritation in case of eye rubbing. Flush with water, if irritation develops. Consult

an ophthalmologist.

Ingestion: No special measures required. Seek medical attention if symptoms develop.

## 5. FIRE-FIGHTING MEASURES

Unsuitable extinguishing: Direct water jet.

Suitable extinguishing: Dry powder fire extinguishers (class A, for solids)

Special procedure: not applicable

Special fire hazard: By burning, some toxic gases (CO, CO<sub>2</sub> and others) can be formed.

Specific protective measures: Gas mask or breathing apparatus

#### 7. HANDLING AND STORAGE

Handling recommendations: Like all foams, a proper ventilation is imperative if this material is subject to

change.

Avoid static electricity, earth all equipment.

Fire hazard: Keep away from immediate and dangerous sources of ignition. Danger of

electrostatic charges when stored in very dry areas.

Storage: Store in a well ventilated room with temperature < 40 °C.

Store in a dry and clean place in its original packaging. Do not expose to UV radiation nor expose (in)directly to sunrays or other sources of heat or external

contamination.

Packaging to avoid: Unventilated package



Last Update: 23.01.2025

# Cross-linked Thermoplastic foams produced by NMC

# 8. PERSONAL PROTECTION

FOR INDUSTRIAL USE

Individual protection equipment: The use of gloves, protective glasses and dust masks and the use of dust

extraction equipment is recommended for sawing, milling, grinding and

sanding.

Respiratory protection: Dust masks are recommended during sawing, milling, grinding and sanding.

Hands protection: Gloves are recommended during sawing, milling, grinding and sanding.

Eyes protection: Protective glasses are recommended during sawing, milling, grinding and

sanding.

Body and skin protection: not applicable

#### 13. DISPOSAL CONSIDERATION

Waste treatment: The foam can not be recycled.

#### **14. TRANSPORT INFORMATION**

Transport in ventilated trailers only.

## **16. OTHER INFORMATION**

Sections 6. Accidental release measures

9. Physical and chemical properties

10. Stability and reactivity

11. Toxicological information

12. Ecological information

15. Regulatory information

do not contain any additional relevant information on the products mentioned in section 1.

The information given in this safety information appendix is accurate to the best of our knowledge, but without any guarantee. It is given in good faith based on the current state of knowledge and experience. It is issued in respect of safety requirements and does not purpose to provide information on the quality of the material.