

PRODUCT SPECIFICATION

NOMAPACK® PLANK



NOMAPACK® Planks are NMC's laminated and flexible PE foam sheets for special requirements.

The extremely shock absorbing properties of the material provide an effective protection against impact, which makes NOMAPACK® Plank an easy choice to protect efficiently your product.

PRODUCT FEATURES

- › Non cross-linked extruded PE-LD foam
- › Closed cell structure with skin
- › Low water absorption and water-vapour transmission rate
- › Very good resistance to solvents, fuel oil and other chemicals
- › High resiliency and flexibility
- › Excellent cushioning behaviour
- › Temperature stability from -40°C to +90°C
- › Good thermal insulation properties
- › Antistatic version available
- › 100% recyclable
- › Odour and dust free
- › Available in different lengths and thicknesses from 20 to 100 mm
- › Standard width of 1210 mm
- › Standard density: from 22 kg/m³ to 200 kg/m³
- › Possibility to combine different densities within the same plank
- › Standard colours: white, grey and black
- › Other sizes, densities or colours on demand

PRODUCT SPECIFICATION

NOMAPACK® PLANK

Type	Length	Width	Thickness	Colour	Density	Packaging	Lager/		Item code	MOQ	Lead time
							kg/m ³	pc/pallet	best.	m ³ /pc	pcs
2400 x 1210 x 30 mm	2400	1210	30	white	30	65	B	0,09	3014717	57	10 - 15
2400 x 1210 x 32 mm	2400	1210	32	white	30	52	L	0,09	3014718	52	10 - 15
2400 x 1210 x 32 mm	2400	1210	32	black	30	57	B	0,09	3014719	57	10 - 15
2400 x 1210 x 32+3 mm HD	2400	1210	35	black	30+60	55	B	0,10	3014722	55	10 - 15
2400 x 1210 x 50 mm	2400	1210	50	white	30	40	L	0,15	3014726	40	10 - 15
2400 x 1210 x 50 mm	2400	1210	50	black	30	40	B	0,15	3014727	40	10 - 15
2400 x 1210 x 50 mm	2400	1210	50	black	60	40	B	0,15	3014729	160	25 - 30
2400 x 1210 x 100 mm	2400	1210	100	white	30	20	B	0,29	3014714	40	10 - 15
2400 x 1210 x 100 mm	2400	1210	100	black	30	20	B	0,29	3014713	57	10 - 15

NMC Sverige AB

Stenstorpsvägen 35
SE – 305 75 Getinge
+46 35 588 00
info@nmc.se



www.nmc-nomafoam.com